

Bellows Suction Cups with Sealing Ring

Suction area (Ø) from 33 mm to 200 mm



Bellows Suction Cups with Sealing Ring

Suitability for Industry Specific Applications

Applications

- Handling of workpieces with uneven surfaces, such as wooden boards with grooved structure or sawed surface
- Handling of cardboards with uneven surfaces made possible by folds
- Energy-efficient handling of workpieces despite uneven workpiece surfaces

Design

- Suction cups from the series FSGA and FSGPL with integrated sealing ring
- Bellows suction cup FSGPL with 1.5 folds with vulcanize insert
- Suction cup FSGA with 1.5 folds, consists of suction cup FGA and a suction cup connection nipple (connection nipple attached)

Product Highlights

- Standard bellows suction cup with integrated sealing ring for use on uneven surfaces, easy changeover
- Energy-efficient handling despite uneven workpiece surface thanks to optimally sealing of sealing ring and bellows suction cup
- Sealing rings made of adaptable and wear-resistant special material guarantee long service life and flexible use

Designation Code Bellows Suction Cups with Sealing Ring

FSGPL	-	100	-	NBR-55	-	G1/2-IG	-	DR
1		2		3		4		5

1 - Abbreviated designation

Code	Version
FSGA	1.5 folds
FSGPL	1.5 folds

2 - Suction area

Code	Diameter in mm
33...200	ø 33 to 200

3 - Material and Shore hardness

Code	Material
NK-45	Natural rubber
NBR-55	Nitrile caoutchuc

4 - Connection

Code	Connection
G1/4-AG	G1/4-AG (AG = male (M))
G1/4-IG	G1/4-IG (IG = female (F))
G1/2-IG	G1/2-IG

5 - Product addition

Code	Type
DR	Sealing ring

Bellows suction cup with sealing ring, available in various diameters, delivered with sealing ring glued on.

Bellows Suction Cups with Sealing Ring

Suction area (Ø) from 33 mm to 200 mm

Ordering Data Bellows Suction Cups with Sealing Ring

Type	Part no.
FSGA 33 NK-45 G1/4-AG DR	10.01.06.01666
FSGA 33 NK-45 G1/4-IG DR	10.01.06.01668
FSGA 53 NK-45 G1/4-AG DR	10.01.06.02928
FSGA 78 NK-45 G1/4-AG DR	10.01.06.02980

Type	Part no.
FSGPL 100 NBR-55 G1/2-IG DR	10.01.06.02978
FSGPL 120 NBR-55 G1/2-IG DR	10.01.06.02993
FSGPL 150 NBR-55 G1/2-IG DR	10.01.06.02672
FSGPL 200 NBR-55 G1/2-IG DR	10.01.06.02985

Technical Data Bellows Suction Cups with Sealing Ring

Type	Suction force (-600 mbar) [N]	Pull-off force [N]	Volume [cm ³]	Workpiece radius min. (convex) [mm]	Hose diameter (recom.) d [mm]	Nipple family
FSGA 33 NK-45 G1/4-AG DR	-	-	-	40	-	N 018
FSGA 33 NK-45 G1/4-IG DR	-	-	-	-	-	N 018
FSGA 53 NK-45 G1/4-AG DR	52	95	29	100	6	N 018
FSGA 78 NK-45 G1/4-AG DR	138	218	80	100	6	N 019
FSGPL 100 NBR-55 G1/2-IG DR	-	-	150	100	12	-
FSGPL 120 NBR-55 G1/2-IG DR	-	-	291	150	12	-
FSGPL 150 NBR-55 G1/2-IG DR	370	500	444	250	12	-
FSGPL 200 NBR-55 G1/2-IG DR	-	-	-	-	12	-